



ATR BR

Compact Refractometer

The stand-alone critical angle refractometer with excellent price performance ratio

473

SH SCHMIDT HAENSCH 3595r. 90.0

SPECIFICATIONS	ATR-BR
Measuring scales	Refractive Index (RI), Sucrose (%Brix), others on request
Measuring range	1.32000 - 1.54000 RI / 100% Brix
Resolution	0.00001 RI / 0.01% Brix
Precision	Measuring range 1.32 - 1.44: \pm 0.00002 RI / \pm 0.01% Brix * Measuring range 1.44 - 1.54: \pm 0.00003 RI / \pm 0.01% Brix *
Reproducibility	± 0.00001 RI / ± 0.01% Brix
Ambient temperature	+ 10° to + 40°C
Automatic temperature compensation	+ 5° to + 50°C
Temperature measurement	NTC sensor for measurement of sample temperature placed inside the prism
Technical control sample	No control
Measurement mode	Single measurement
Prism	Sapphire
Light source / wavelength	LED, interference filter 589 nm
Display	Back-lit LCD, 16 x 16 characters
Operation	20 key membrane including function keys
Interfaces	1 x RS232 C serial and parallel
Standard model	ATR-BR
Conformity	International Pharmacopoea, ASTM, AOAC, DIN, FDA, ICUMSA and others
Highlights	Stand alone device; high quality and precision; very stable measurements: user friendly operation; excellent price performance ratio, very flat and small sample room for easy cleaning

* Standard conditions (589 nm, 20°C)

Refractometer applications

The applications of Refractometers are highly diverse.

Applications often used

- Determination of refractive index
- Determination of dry substance
- Determination of mass percent
- Brix measurement
- Qualitative analysis identification of samples
- Quantitative analysis of dissolved solids in water or other solvents

Typical applications of the model

- Sugar industry
- Beverage industry
- Food industry
- Chemical industry





Schmidt + Haensch GmbH & Co.

Waldstraße 80-81, 13403 Berlin, Germany Tel: + 49 (0 30) 417072-0, Fax: + 49 (0 30) 417072-99 sales@schmidt-haensch.de, www.schmidt-haensch.com